
Special Instruction For The 4 IN 1 Series.

1.1 Overview for 4 in 1 products(Support AHD/ CVI/ TVI/ CVBS output)

Basic on single HD Analog coaxial series,(AHD/TVI/CVI/CVBS series), the 4 in 1 series have combined the 4 single output signal together,it can be switched the video signal freely between the AHD/TVI/CVI/CVBS by shortcut commends. This gives great convenience for all application, reduce cost, and easy for maintenance.

1.2 Two ways to switch the video signal

A. Call twice preset 102 to enter the Sub OSD menu.

Press “Zoom+” or “Zoom-” to move the option to the item 1.

Press the “Focus+” or ”Focus-” to switch to the signal output needed,

Then press “ zoom+ or Zoom- to the item 6“ RETURN”

Call twice 102 again to exit from the Sub OSD menu.

B. Direct shortcut commend to switch the video output signal needed. Please

Reference to the below table for details.

Remark:

Please do not change the parameter of the Sub OSD menu randomly to avoid any unexpected happen.

Please reboot the PTZ after switch the video signal output.

1.3 Shortcut commend list.

Shortcut commends are complaine with Pelco D and its Extended protocol. User can use the shortcut commend to enable the function directly.

Preset No.	Function	Preset No.	Function
81 (41)	Auto day/ night	97	Call tour 2
82 (42)	Switch to night	98 (38)	Call tour 1
83	Switch to day	99 (39)	Pan scan
84	Force on far light	Twice 137	Switch to AHD
85	Force on near light	Twice 138	Switch to TVI
92	A-B Scan	Twice 139	Switch to CVI
94	OSD off	Twice 140	Switch to CVBS
95	OSD on	Twice 115	Switch to NTSC
96	Call tour 3	Twice 116	Switch to PAL

Remark:

Because the limit of COC protocol,it is possible that some of the shortcut commend are not valid when connected to some of the controlled equipment.

If no video or video is stuck in black and white, please make sure the video output of the signal, the TV system (NTSC/Pal) between the PTZ and the controlled equipment to be consistent, if not, please adjust accordingly.